



### Warm air heaters / HT2000 VNO & VNG heater range Oil and Gas fired cabinet heaters

Energy efficient

Fast warm up

Building Regulation, ECA & CE Compliant Models

Comfort and warmth when and where needed

Controlled automatic operation

Extended guarantees

Simple installation

Compact design



**“Taylor” made solutions from the company with the know - how**



**Oil fired heaters:**  
Suitable for ducted or free blowing applications using 35 seconds fuel oil (and 28 seconds fuel oil for lower output heaters).



**Gas fired heaters:**  
Suitable for ducted or free blowing applications using natural gas or lpg.

**Warm air heating / HT2000 - VNO & VNG Heaters**  
Product range information:

These high efficiency, fuel efficient cabinet heaters comply with all current CE, ECA and building regulations. Forced draught gas or pressure jet oil burners complete with flame monitoring safety controls and optimised control ensure these heaters are ideal for free blowing and ducted applications where space is not at a premium. Mostly vertically mounted these heaters can also be supplied in horizontal (H) or reverse flow (RF) configurations.

**Visit us online: [www.harrytaylor.co.uk](http://www.harrytaylor.co.uk)**

# Warm air heaters / HT2000 VNO & VNG heater range

## Oil and Gas fired cabinet heaters

Warm air heating is long proven as a comfortable low cost heating solution for most industrial, commercial & horticultural buildings. Design experience accumulated over more than forty years has combined with modern computer integrated technology to provide a range of cabinet heaters renowned for robust construction, reliability and economy.

### Technical data:

Model		100	125	150	200	250	300	400	500	600	700	800	1000	1200	1300	
Output	kW	29	36	43	58	73	86	117	132	177	205	235	284	350	381	
ECA Approved		✓	✓		✓	✓		✓	✓	✓		✓	✓	✓		
Electrics	Std	230/1/50						415/3/50								
	Optional	n/a			415/3/50			230/1/50			n/a					
Overall Dimensions	Height	mm	1890	1980	1980	2230	2560	2560	2745	2745	2940	2940	3025	3025	3782	3782
	Width	mm	660	660	660	660	660	660	740	740	916	916	1100	1100	1244	1244
	Depth	mm	1011	1011	1011	1287	1287	1287	1517	1517	1895	1895	2130	2130	2130	2130
Flue Diameter	mm ø	125	125	125	150	150	175	175	175	200	200	225	225	250	250	
Nett Weight	kg	196	196	196	241	243	243	330	332	525	540	630	646	1090	1090	

Note: Weights and dimensions refer to vertical heaters only. For details of horizontal and reverse-flow units please contact our sales office

### Specification:

**Application:** A range of oil and gas fired cabinet heaters, generally vertical floor mounted but also available in horizontal and reverse flow configuration suitable for factories, workshops, warehouses, greenhouses and many other commercial premises.

**Building Regulations & ECA Approval:** All our cabinet heaters are designed with fuel efficiency in mind and meet the efficiency requirements of Part L2B of current Building Regulations as well as applicable CE legislation. Additionally most models within the range have been rated to meet the Government's energy efficiency criteria for inclusion into the Enhanced Capital Allowance scheme.

**Construction:** The casing is robotically formed from electro zinc coated steel sheet and finished with a durable stove hardened epoxy polyester powder paint whilst the combustion chamber/heat exchanger is formed and welded from 304/316 stainless and grade HR4 steel.

**Burner:** High efficiency pressure jet oil or forced draught gas suitable for operation on 35 second light fuel oil, kerosene (most models), natural gas or lpg propane and complete with flame monitoring safety controls.

**Controls:** Heaters are ready for automatic operation after the simple connection of the time and temperature control. We offer a fully optimised control which includes a secure entry code facility, temperature dependant start time, digital time switch with override facility, electronic day & frost protection thermostats and can be set to run on "fan only" to enable summer air movement.

**Air Distribution:** Via a quiet yet powerful centrifugal fan set with directional nozzles which discharge the warm air directly into the area to be heated. Alternatively a spigot outlet can be provided for ductwork systems with filter and fresh air inlet options available.

**Testing:** Every heater is individually inspected, test fired and safety function tested prior to despatch.

**Guarantee:** heaters are provided with one of the most comprehensive guarantee packages available -

Year One: Parts and labour

Year Two: Parts

Ten Year: Combustion chamber heat exchanger warranty

**Harry Taylor Southern office:**  
Kitsons Works, Aylesbury Road,  
Bromley, Kent,  
BR2 0QZ, UK

**Southern office tel:** 020 8464 0915  
[southernoffice@harrytaylor.co.uk](mailto:southernoffice@harrytaylor.co.uk)

**Harry Taylor Northern office:**  
Guide Bridge Mill, South Street,  
Ashton - under - Lyne, Lancs,  
OL7 0HU, UK

**Northern office Tel:** 0161 308 4550  
[northernoffice@harrytaylor.co.uk](mailto:northernoffice@harrytaylor.co.uk)

 **Harry Taylor**  
[www.harrytaylor.co.uk](http://www.harrytaylor.co.uk)