

## Warm air heaters / HT2000 OUH heater range

Oil fired suspended heaters

High efficiency

CE & Building Regulations Compliant

Optional sealed combustion circuit

Heat exchanger made of T430 stainless steel

Automatic operation

Optimised control

Centrifugal options available

Space saving off floor installation



“Taylor” made solutions from the company with the know - how



**Axial fan heaters**

For conventional cross flow warm air discharge.



**Centrifugal fan heaters**

For ducted heating systems.

**Warm air heating / HT2000 - OUH heaters**

**Product range information**

These high efficiency, fuel efficient suspended heaters comply with current CE and building regulations. With automatic ignition, room sealed combustion and optimised control they are ideal space saving heaters.

Visit us online: [www.harrytaylor.co.uk](http://www.harrytaylor.co.uk)

# Warm air heaters / HT2000 OUH heater range

## Oil fired suspended heaters

Compact, quiet & highly efficient HT2000 OUH oil fired unit heaters provide cost effective heating for many commercial & industrial buildings. Offering space saving 'off-floor' mounting OUH A oil unit heaters discharge warmth directly into the space to be heated in a conventional cross-flow manner. OUH C versions are suitable for ducted systems.

Model			75	100	150	200	
Output (nominal)	High Fire (Max)		kW	20	30	45	60
	Low Fire (Min)		kW	16	24	34	45
Airflow	Volume	OUH F	m <sup>3</sup> /s	0.7	0.82	1.19	1.94
		OUH C	m <sup>3</sup> /s	1.0	0.82	1.19	1.88
	Throw	OUH F	m	8.5	16	25	34
	Fan static	OUH C	Pa	275	305	275	384
Electrics	Supply	Standard	V/ph/Hz	230/1/50			
	Run current	OUH F	amp	0.94	0.46	0.48	1.7
		OUH C	amp	4.3	4.33	5.54	8.0
Fuel Oil	Connection		BSP/Rc	1/4			
	Consumption		l/h	2.18	3.18	5.32	6.70
Mounting Height	OUH F	Min	m	2.50		3.00	
		Max	m	3.00		5.00	
Overall Dimensions	Height		mm	806	1043	1049	1049
	Width		mm	555	780	780	780
	Depth	OUH F	mm	868	1106	1115	1150
		OUH C	mm	1163	1470	1469	1469
Installation Clearances	Top		mm	1000			
	Side		mm	500			
			mm	400			
Flue diameter			mm Ø	400			
Combustion Air Spigot			mm Ø	400			
Maximum Combustion Duct Length			m	120	100	81	21
Noise Level - OUH F models			dB(A)	46	54	52	53
Nett Weight	OUH F		kg	53	126	126	126
	OUH C		kg	91.5	142	142	142



**Harry Taylor South:**  
 Kitsons Works, Aylesbury Road  
 Bromley, Kent  
 BR2 0QZ, UK

**Southern Office Tel:** 020 8464 0915  
 southernoffice@harrytaylor.co.uk

**Harry Taylor North:**  
 Guide Bridge Mill, South Street  
 Ashton-Under-Lyne, Lancs  
 OL7 0HU, UK

**Northern Office Tel:** 0161 330 5632  
 northernoffice@harrytaylor.co.uk

