



Warm air heaters / HT2000 heater range Room Sealed Low-Nox unit heaters

ErP Ready 2021

Low Nox

CE & Building Regulations Compliant

Sealed Combustion Circuit

Modulating Burner

Automatic Operation

Digital Optimised Heating Controls

Frost Protection

Summer Fan operation



ACCREDITED
SUPPLIER

“Taylor” made solutions from the company with the know - how

Overview

The ErP 2021 compliant suspended LX range of unit heaters benefits from the same design as the popular LNVx range: its construction, performance, and aesthetics, finished with the popular epoxy powder RAL 7015 stove baked paint.

Our most advanced heater the LX is ergonomically designed with low NOx levels to provide efficient and cost effective heating solutions for any industrial and commercial properties whilst being built with heating engineers in mind.

Product Features

- Wide range of sizes, twelve capacities from 15 to 140kW
- Standard axial fan heater throws up to 45m.
- Compact space saving dimensions, designed to be room sealed or power flued with vertical or horizontal option.
- Most comprehensive model range including Axial Fan, Centrifugal Fan (with or without fan plenum), Axial fan downflow, Bi-Directional and Duct Package.
- Low NOx and high energy output with highest efficiency without condensing, simple and efficient high - low burner control.
- Designed for strength, rigidity and long service life with minimal noise levels.

Specification

- Heat exchanger manufactured as standard from aluminised steel tube with swaged and expanded connections into a combustion gas collection box, no welding is used to minimise stress on components.
- The four pass tubular heat exchanger can be specified with upgrade to 409 and 316 stainless steel.
- Individual in shot burners per heat exchanger tube to be fitted with Resistohm Helical Low NOx inserts capable of maximum continual 1300°C operation.
- Heaters will be capable of use with G20 Natural Gas or G31 LPG with injector change.
- Supplied with a modulating gas valve assembly as standard to achieve designed coverage and throw the supply fan airflow will remain constant through the modulating operation.
- Casing designed for rigidity and low noise, anti-vibration mounts utilized to secure the main fan assemblies.
- Units complete with easy access swing out burner wiring panels.
- NOx Levels will be less than 70mg/kWhr.
- Heater casing protected by epoxy powder coat stove baked paint RAL 7015.



HARRY TAYLOR

Celebrating 100 Years



INDUSTRIAL
HEATING
SERVICES



EVAPORATIVE
COOLING
SOLUTIONS

Technical Data

Model				50	70	90	100	115	150	170	200	250	300	410	490		
Output (nominal)	Nat Gas	High Fire (max)	kW	15.2	19.2	24.6	30.3	35.0	39.2	52.7	59.6	69.4	87.0	118.9	138.2		
		Low Fire (min)	kW	7.9	11.2	11.7	16.1	17.3	19.6	24.2	30.5	37.0	52.7	62.6	69.1		
	LPG	High Fire (max)	kW	15.9	18.8	27.0	30.0	33.2	39.9	53.9	59.2	69.4	90.4	119.4	138.5		
		Low Fire (min)	kW	7.9	9.1	13.0	14.9	16.7	21.3	23.8	25.8	37.5	53.3	49.4	81.9		
Input (nett CV)	Nat Gas	High Fire (max)	kW	16.04	20.05	26.8	33.2	38.4	42.5	57.6	64.8	75.9	93.3	127.5	149.9		
		Low Fire (min)	kW	8.2	11.4	12.5	16.7	18.3	20.7	26.0	32.2	39.5	56.3	66.5	72.8		
	LPG	High Fire (max)	kW	17.8	20.9	29.9	32.8	36.6	43.5	58.7	65.6	74.9	96.2	130.0	150.4		
		Low Fire (min)	kW	8.6	9.6	13.8	15.7	17.7	22.3	25.7	28.0	39.5	58.2	51.0	86.2		
NOx Seasonal (Gross)			mg/kWh	52.0	60.0	51.7	59.0	66.8	37.6	48.3	60.2	53.9	66.0	64.2	61.2		
Seasonal Space Efficiency			% hs,h	76.5	78.9	79.5	80.7	80.5	78.1	79.2	79.0	80.5	82.0	80.5	80.0		
Airflow Volume		LX F & F/V & C	m ³ /s	0.39	0.56	0.78	0.97	1.11	1.18	1.51	1.83	1.94	2.81	3.56	3.75		
		LX D	Min	m ³ /s	0.39	0.56	0.78	0.97	1.11	1.18	1.51	1.83	1.94	2.81	3.56	3.75	
			Max	m ³ /s	0.43	0.62	0.86	1.07	1.22	1.30	1.67	2.02	2.14	3.09	3.91	4.13	
Airflow	Throw Static	LX F	m	10	14	20	25	28	30	35	38	42	44	45	45		
		LX C	Pa	220	320	220	220	200	150	250	250	250	180	290	250		
Electrics	Supply	Standard	V/ph/Hz	230/1/50													
		Optional*	V/ph/Hz	400/3/50 *on Centrifugal Units Only. 3Ph units shown in brackets ()													
	LX F	Run	amp	0.9	1.0	1.0	1.2	1.7	1.3	1.8	2.5	2.4	3.2	46	4.7		
		Start	amp	1.9	2.0	2.0	2.4	4.0	2.7	4.0	5.0	4.0	6.0	8.0	8.0		
	LX C	Run	amp	2.0	3.1	4.2	4.3	4.7	5.8	7.6	10(4.8)	10(5.3)	12.8	17(9.2)	20(4.8)		
Start		amp	5.0	8.5	13.1	14.0	15.6	18.0	26.3	29(16.5)	38(18)	31.0	40(29.8)	44(33.6)			
Fuel	Connection		BSP/Rc	¾"												1"	
	Nominal Inlet Pressure	Nat Gas	mbar	20.0													
		LPG	mbar	37.0													
	Consumption	Nat Gas	m ³ /h	1.70	2.17	2.83	3.51	4.06	4.49	6.09	6.85	8.03	9.88	13.50	15.86		
LPG		m ³ /h	0.73	0.86	1.22	1.34	1.50	1.78	2.40	2.69	3.06	3.94	5.32	6.15			
Mounting Height	LX F & F/Duo	Min	m	2.5						3.0							
		Max	m	3.0				3.5		5.0							
	LX F/V Downflow	Min	m	2.5	4.0				5.0				6.0				
		Max	m	3.0	6.0			7.0			8.0		10.0	12.0			
Overall Dims	LX F	Height	mm	450	500	570	670	532	720	684	760	912	810	975	1140		
		Width	mm	997	997	997	997	1325	997	1325	1325	1325	1950	1950	1950		
		Depth	mm	859	869	819	834	918	839	938	915	915	938	915	915		
Install Clearance	All	Top	mm	200													
		LH Side	mm	200													
		RH Side	mm	1000													
		Rear	mm	400													
Flue	Diameter	mm Ø	80	80	80	100	100	100	100	130	130	130	130	130			
	Max	Flue Only	m	12													
	Length	Room Sealed	m	6													
Combustion Air Spigot			mm Ø	80	80	80	100	100	100	100	130	130	130	130	130		
Noise Levels		LX F	dB(A)	48	47	47	47	50	58	59	59	60	63	64	64		
		LX C	dB(A)	55	55	54	54	N/A	60	60	62	62	66	67	67		
Nett Weight		LX F	kg	60	73	77	81	84	103	122	135	149	202	238	286		
		LX C	kg	71	84	86	94	108	122	143	170	213	329	364	430		

Harry Taylor South:

Kitsons Works, Aylesbury Road,
Bromley, Kent,
BR2 0QZ, UK

Harry Taylor North:

Guide Bridge Mill, South Street,
Ashton-under-Lyne, Lancs
OL7 0UH, UK



Harry Taylor

www.harrytaylor.co.uk

Tel: 020 8464 0915

Email: southernoffice@harrytaylor.co.uk

Tel: 0161 3084550

Email: northernoffice@harrytaylor.co.uk

The company with the know-how